

TECHNICAL DATA

FORTFLAT 6012

MARINE EPOXY ANTIFOULING PAINT



A hard protective antifouling paint for marine purpose with Flat appearance

PRODUCT FEATURES

- Attractive finish
- Effective non-slip coating
- Cost effective
- Can be over-glazed

SPECIFICATION

| | |
|-------------------------|--|
| TYPE | MODIFIED EPOXY |
| ACTIVE INGREDIENT | CURPROUS OXIDE |
| SOLVENTS | MINERAL SPIRITS |
| PRACTICAL COVERAGE | APROX.85 SQ.F |
| DRYTIMES@70F and 50% RH | RECOAT :4 HOURS LAUNCH AFTER 24 HOURS |
| SHELF LIFE | 4 YEARS |

SURFACE PREPARATION:

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with commercial detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry
Remove all loose rust or deteriorated coatings by scraping or wire brush.

APPLICATION:

Stir thoroughly. Thinning not needed for brush or roller. If sprayed, thin up to 15% with acetone. Apply with good quality brush, roller or spray gun. The coating may be placed in service in 24 hours

CLEAN UP: Clean brush, roller, and other tools with mineral spirits.

PACKING: 20litre pack

SPECIAL PRECAUTIONS - HEALTH & SAFETY: Do not take internally. Avoid contact with eyes and prolonged contact with skin or breathing of spray mist. Use a dust/particulate respirator while spraying or sanding. Close containers after each use. USE COMPLETELY OR DISPOSE OF PROPERLY. Hold unused paint in sealed container for special waste disposal. Do not discard into sewers or waterways. USE ONLY WITH ADEQUATE VENTILATION KEEP OUT OF REACH OF CHILDREN

