

## TECHNICAL DATA

### PROCOAT RUST PROOF PAINT

PROCOAT is a super-tough, high-performance, rust inhibitive coating which is highly effective and guaranteed to stop rust and prevent corrosion for the life time . It has excellent rust preventing properties because of its balanced formulation of special resin and rust inhibiting filler.

#### USES

PROCOAT is a airtight/water tight seal that stops the oxidation process dead in its tracks and prevents any future rust. This non-porous seal is 100% rustproof and prevents most types of corrosion. It is highly resistant to water, wastewater, salt water, salt, grease, sludge, oil, gasoline, fuel, lubricants, freeze-thaw stretching and abrasion.

#### ADVANTAGES

- 1) Excellent Adhesion
- 2) Long life
- 3) Uniform Thickness of Coat
- 4) Fast Drying
- 5) Good Adhesion promoter for subsequent coat

#### PROPERTIES

Finish		: Flat
Colour		: Red
% solid by weight		: 70 ± 3%
Dry to touch		: 5 minutes
Dry to handle		: 10 minutes
Flash point		: 37°C
Theoretical Coverage at 30 microns DFT		: 15.00 m <sup>2</sup> / ltr

#### SURFACE PREPERATION

Before application of PROCOAT, the surface should be free from oil, grease, rust etc.

Note: Proper ventilation is a must during application and drying

#### PRECIDING COAT

None



## TECHNICAL DATA

### STORAGE

The product should be kept in well ventilated place, protected from heat and direct sunlight. Containers must be kept tightly closed.

### PACKAGING

PROCOAT is available in 5 US Gallon.

### NOTE

All information is given in good faith on the results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since we don't have any control on site conditions and its uses.

