

TECHNICAL DATA

DRY BITUTEX-SB

SOLVENT BASED BITUMINOUS PROTECTIVE COATING

DRY BITUTEX –SB is a solvent based bituminous protective coating that dries to form a highly flexible seamless tough impermeable water and vapor proof membrane.

USES

- Water proofing /damp proofing of most substrates.
- Waterproofing and damp proofing of below block work, concrete structures and pipes prior to back filling
- Protection of foundations , columns and beams.
- Water proofing and protection of structures.
- For use as an adhesive on wood blocks , wood mosaics, insulation boards etc.
- Can be used as vapor barrier.
- Curing agent for fresh concrete.
- For damp proofing and tanking structures.
- Waterproofing for interior and exterior walls
- Protective coating for steel surfaces
- Curing agent for freshly laid concrete surfaces
- Water proofing of wet areas.

FEATURES

- Joint less membrane when it cures.
- Economical and easy to apply
- Single component-cold applied and ready to use
- Excellent adhesion to most building substrates
- Can be applied on damp substrates.
- Excellent resistance against soil acids.

COFIRMATION

BITUTEX-SB confirms to ASTM standards and British standard Code of practice. “protection of buildings against water from the ground, Damp proofing and adhesive used in buildings.



TECHNICAL DATA

SPECIFICATION

Density	0.85-0.88g/cc
Color	black
Water content	0.5% (max)
Toxicity	Non-Toxic
Surface Dry (Hrs)	2 hours depends upon the climatic conditions.
Coverage	2 Sq. Meter / Liter per coat
Complete dry	24 hours

APPLICATION PROCEDURE.

SURFACE PREPERATION

All surfaces must be sound, clean and free from dust, oil or grease and other loose materials. Surface may be damp but there should not be any standing water and can be applied to fresh freshly cast concrete too.

First coat should be light and the successive coat shall be applied only after the drying of the previous coat.

Coverage: 2 to 4 sq.m /Liter per coat (depends upon the surfaces to be applied)

STORAGE

Shelf life one year in closed container.

PACKING:

Available in 20 litres and 200 litres drums.

HEALTH AND SAFETY:

BITUTEX –SB is non-toxic and no health hazards. Should wear necessary protective cloths while using .

