

## TECHNICAL DATA

# PRIMEX-EPDM

## EPDM LAP ADHESIVE

PRIMEX – EPDM is a low viscosity solution of synthetic rubber and resins combined with organic, halogen free solvents. It is intended for use for the lap joint.

### APPLICATION PROCEDURE:

DRY PRIME – EPDM is suitable for sealing the laps . All surfaces to be primed must be firm, flat, dry and free from dust and grease. PRIMEX is applied to the substrate with a brush or lambs wool roller. Laps should be at least 50mm and spread PRIMEX across the lap area.

### COVERAGE RATE:

The coverage rate for PRIMEX is between 200g/m<sup>2</sup>, dependant upon the evenness and porosity of the substrate and the type of application.

### IMPORTANT INFORMATION:

- PRIMEX will keep for 6 months at +10°C to +25°C in the unopened container.  
Avoid direct sunlight.  
Stir thoroughly before use.
- The minimum application temperature is +5°C.
- Surfaces and tools can be cleaned
- PRIMEX is inflammable and should be kept away from naked flames.  
Smoking is not permitted in the vicinity.
- Workers area should be ventilated and containers kept closed to prevent inhalation.

### PACKAGING:

PRIMEX is packed in 4.5 kg tins/20 ltr pail.

